

D-Net™ 9575 AA

¾" impact sprinkler with unique 3D arm and adjustable arc for part circle irrigation.



Very High Water
Distribution
Uniformity



Road Guard



Easy Operation &
Maintenance

Applications



Open field crop
edge irrigation



Roof
cleaning

Benefits & Features

Road guard

- ✓ A simple adjustable arc enables to modify manually, the sprinkler from 360 degrees to any part-circle watering, for irrigation on the edges of the field

Very high water distribution uniformity & Higher yield

- ✓ Innovative 3D diffusion arm, ensures excellent water distribution uniformity, resulting uniform crop yield
- ✓ Special design of the D-Net™ 9575 AA, guarantees maximum water-use efficiency

Robust product & Long lasting performances

- ✓ D-Net™ 9575 AA has a special design that makes the sprinkler resistant to wear and ensures high performance throughout the long product life

Reduced labor cost & Easy maintenance

- ✓ Versatile installation. Can be installed on solid sets or on removable field stands
- ✓ Easy to maintain. A special nozzle key is designed to allow simple cleaning of the nozzles
- ✓ D-Net™ 9575 AA is made of UV-protected materials, making it durable under all climate conditions and with any applied

Specs. & Recommendations

- ½" Impact sprinkler with unique 3D arm and Adjustable Arc, for part circle coverage irrigation
- **2 different flow rates:** 850, 1030 L/H
- **Nominal flow rate at:** 3.0 bar
- **Recommended pressure range:** 2.5 - 4.0 bar
- **Water trajectory angle:** 24 Degrees
- Water distribution is achieved by a single front nozzle and the setup of the adjustable arc
- **1 type of inlet connector:** ¾" male threaded
- Color coded of the nozzle for easy identification of the flow rate
- Made of UV-protected materials, durable to all climate conditions and nutrients injected in agricultural applications
- Recommended filtration, according to Netafim's instructions*

***Note:** Filtration method shall be selected based on the type and concentration of the dirt particles contained in the water. Wherever sand exceeding 2 ppm exists in the water, a Hydrocyclone shall be installed before the main filter. Wherever sand/ silt/ clay solids exceed 100 ppm, pre-treatment shall be applied according to Netafim™ instructions



→ PERFORMANCE DATA

NOZZLE SIZE (MM)	CODE COLOR	WORKING PRESSURE (BAR)	FLOW RATE (L/H)	WETTED RADIUS* (M)
FRONT NOZZLE 3.57	BLUE	2.5	776	11.5
		3.0	850	12.0
		3.5	918	12.0
		4.0	982	12.5
FRONT NOZZLE 3.96	GREEN	2.5	940	12.0
		3.0	1030	12.5
		3.5	1112	12.5
		4.0	1189	13.0

* At least 0.5 mm/h

→ PACKAGING DATA




MODEL	QUANTITY P/BOX UNIT	BOX SIZE (CM X CM X CM)	BOX WEIGHT (KG)	BOXES P/PALLET	TOTAL UNITS P/PALLET	PALLET WEIGHT (KG)
D-NET™ 9575 AA	40	54 X 20 X 48	9.4	20	800	190

→ CATALOG NUMBERS

NOZZLE SIZE (MM)	NOZZLE CODE COLOR	FLOW RATE (L/H) *	CATALOG NUMBER
3.57	BLUE	850	60100-002190
3.96	GREEN	1030	60100-002191




*Nominal flow rate at 3.0 bar working pressure

→ NOZZLES INFORMATION

PRODUCT ILLUSTRATION	NOZZLE SIZE (MM)	CODE COLOR	CATALOG NUMBER
	FRONT NOZZLE 3.57	BLUE	60100-002100
	FRONT NOZZLE 3.96	GREEN	60100-002101
	PLUGGED NOZZLE	BLACK	60100-001400

*The catalog number is for full box of nozzles

→ COMPLEMENTARY PRODUCTS

PRODUCT ILLUSTRATION	DESCRIPTION	CATALOG NUMBER
	SOCKET 3/4" - 3/4" FEMALE-FEMALE THREAD	65080-004700
	SPRINKLER ADAPTER 1" AND 3/4" FEMALE THREAD TO 3/4" FEMALE THREAD	60101-000500
	D-NET™ 9575 NOZZLE TOOL	1 UNIT
		60100-003600
		150 UNITS/BOX
		60100-003610

→ SPRINKLER STANDS

NetaStand™

PRODUCT ILLUSTRATION	DESCRIPTION	CATALOG NUMBER
	BASE NetaStand™ FEAMLE THREAD 3/4" - 24 UNITS PER CARTON Order by box: 1 box contain 24 units	60101-000901
	PLASTIC RISER 3/4" MALE FEMALE THREAD 40CM COMPLETE	60101-000650
	NetaStand™ 15M FXN HPPP 3" W/3"CONC 70 SETS PER PALLET	60101-000967