

Streamline™ X

Integral non pressure-compensated high clogging-resistance dripper, for single season applications.

→ 12060 - 12080 - 16050 - 16060 - 16070 - 16080
16100 - 22050 - 22060 - 22070 - 22080 - 22100



Tough



High clogging
resistance



Self-cleaning
labyrinth

/ Benefits & Features

→ Toughness

Streamline™ X is the toughest thin wall dripline ever made, incorporating a unique ribbed surface that acts as a barrier between the ground and the dripline, making deployment and retrieval smoother than ever before.

→ High clogging resistance

Even with challenging water quality, with self-cleaning labyrinth that flushes debris throughout operation.

→ Wide filtration area

Ensures optimal performance even under harsh water conditions, preventing the entrance of sediment into the labyrinths.

→ TurboNet™

Labyrinth ensures wide water passages, to increase flushing efficiency. The water is drawn into the dripper from the stream center, preventing the entrance of sediment into the drippers.

/ Specifications

- ✓ Streamline™ X driplines are available with hole or flap outlet. The 0.35 l/h has a sand barrier so only a hole is possible with this flow.
- ✓ Recommended filtration: depending on dripper flow rate. Filtration method selected based on the kind and concentration of dirt particles contained in the water. Wherever sand exceeding 2 ppm exists in the water, a Hydrocyclone shall be installed before the main filter. Where sand/silt/clay solids exceed 100 ppm, pre treatment shall be applied following Netafim expert instructions.
- ✓ TurboNet™ labyrinth with large water passage.
- ✓ Weldable into thin wall driplines (0.13, 0.15, 0.18, 0.20, 0.25 mm).
- ✓ Injected dripper, very low CV.
- ✓ High UV resistant. Resistant to standard nutrients used in agriculture.
- ✓ Meets ISO 9261 Standards with Israel Standard Institute (SII)-certified production.

→ DRIPPERS TECHNICAL DATA

12060, 16050, 16060, 16070, 22050, 22060, 22070 - 0.13, 0.15, 0.18 mm wall thickness driplines

FLOW RATE*	MAX. WORKING PRESSURE** (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM ²)	CONSTANT K	EXONENT X	RECOMMENDED FILTRATION (MICRON)/(MESH)
0.35	0.8 up to 1.9	0.35 x 0.34 x 23	12	0.116	0.48	130/120
0.80		0.59 x 0.33 x 25	12	0.265	0.48	130/120
1.10		0.51 x 0.44 x 13	14	0.392	0.45	130/120
1.60		0.65 x 0.55 x 13	15	0.568	0.45	130/120
2.20		0.72 x 0.65 x 13	15	0.780	0.45	130/120
2.80		0.84 x 0.73 x 13	15	0.993	0.45	200/80

* Flow rate at 1.0 bar pressure **According to driplines wall thicknesses and inside diameters

→ DRIPPERS TECHNICAL DATA

12080, 16080, 16100, 22080, 22100 - 0.20, 0.25 mm wall thickness driplines

FLOW RATE*	MAX. WORKING PRESSURE** (BAR)	WATER PASSAGES DIMENSIONS WIDTH-DEPTH-LENGTH (MM)	FILTRATION AREA (MM ²)	CONSTANT K	EXONENT X	RECOMMENDED FILTRATION (MICRON)/(MESH)
0.35	1.0/1.1/1.2/1.4	0.35 x 0.34 x 23	12	0.116	0.48	130/120
0.72		0.59 x 0.33 x 25	12	0.238	0.48	130/120
1.05		0.51 x 0.44 x 13	14	0.373	0.45	130/120
1.60		0.65 x 0.55 x 13	15	0.568	0.45	130/120
2.20		0.72 x 0.65 x 13	15	0.780	0.45	130/120
2.80		0.84 x 0.73 x 13	15	0.993	0.45	200/80

* Flow rate at 1.0 bar **According to driplines inside diameter

→ DRIPLINES TECHNICAL DATA

MODEL	INSIDE DIAMETER (MM)	WALL THICKNESS (MM)	OUTSIDE DIAMETER (MM)	MAX. WORKING PRESSURE (BAR)	MAXIMUM FLUSHING PRESSURE (BAR)	KD
12060	11.80	0.15	12.10	1.60	1.8	0.15
12080	11.80	0.20	12.20	1.90	2.2	0.15
16050	16.20	0.13	16.46	0.80	0.9	0.10
16060	16.20	0.15	16.50	1.00	1.2	0.10
16070	16.20	0.18	16.56	1.10	1.3	0.10
16080	16.20	0.20	16.60	1.20	1.4	0.10
16100	16.20	0.25	16.70	1.40	1.6	0.10
22050	22.20	0.13	22.56	0.75	0.9	0.01
22060	22.20	0.15	22.50	0.80	0.9	0.01
22070	22.20	0.18	22.56	0.90	1.0	0.01
22080	22.20	0.20	22.60	1.00	1.2	0.01
22100	22.20	0.25	22.70	1.10	1.3	0.01

→ DRIPINES PACKAGE DATA (ON CARTON COIL)

MODEL	WALL THICKNESS (MM)	DISTANCE BETWEEN DRIPPERS (M)	COIL LENGTH (M)	AVERAGE* COIL WEIGHT (KG)	COILS PER PALLET (UNITS)	COILS IN A 40 FEET CONTAINER (UNITS)	TOTAL IN A 40 FEET CONTAINER (M)
12060	0.15	0.15 to 0.25	3000	22.1	16	640	2240000
		0.30 to 1.00	3200	21.2			2240000
12080	0.20	0.15	2800	24.5	16	640	1792000
		0.20 to 1.00	3000	23.8			1920000
16050	0.13	0.15 to 0.25	3200	24.5	16	640	2048000
		0.30 to 1.00	3600	25.6			2304000
16060	0.15	0.15 to 0.25	2600	21.5	16	640	1664000
		0.30 to 1.00	3000	24.0			1920000
16070	0.18	0.15 to 0.25	2500	22.5	16	640	1600000
		0.30 to 1.00	2800	26.5			1792000
16080	0.20	0.15 to 0.25	2200	23.7	16	640	1408000
		0.30 to 1.00	2500	26.3			1600000
16100	0.25	0.15 to 0.25	1800	23.6	16	640	1440000
		0.30 to 1.00	2000	25.9			1600000
22050	0.15	0.15 to 0.25	2800	26.0	16	640	1792000
		0.30 to 1.00	3000	27.9			1920000
22060	0.15	0.15 to 0.25	2200	23.5	16	640	1408000
		0.30 to 1.00	2400	26.0			1536000
22070	0.18	0.15 to 0.25	1800	23.7	16	640	1152000
		0.30 to 1.00	2000	25.8			1280000
22080	0.20	0.15 to 0.25	1600	23.6	16	640	1024000
		0.30 to 1.00	1800	25.6			1152000
22100	0.25	0.15 to 0.25	1200	22.0	16	640	768000
		0.30 to 1.00	1500	26.6			960000

* Calculated weight average. For further details see "Average Coil Weight Disclaimer".

Drippers flow rate vs. working pressure

In order to calculate the right flow rate of each dripper, under different working pressures, we use the following formula:

$$Q = K * P^X$$

Where:

Q = Dripper flow rate (liters/hour)

K = Constant (each dripper has his singular constant and must be defined by the dripper producer)

P = Real working pressure (meter)

X = Exponent (each dripper has its singular exponent and must be declared and defined by the dripper producer)

*ISO 9261 require from the manufacturer to declare the constant K and dripper exponent

Non-regulated drippers provide flow adequate to the pressure it is exposed to, according to the formula presented above. In order to simplify the calculations and understandings of the linkage between the flow and the pressure, a table with the flow rates at different working pressures is presented here for each of the drippers presented in this document.

Flow rate (l/h) vs. Pressure (bar)

0.13, 0.15, 0.18 mm wall thickness dripperlines

FLOW RATE* (L/H)	PRESSURE (BAR)										
	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.4
0.35	0.20	0.22	0.25	0.27	0.29	0.31	0.33	0.35	0.37	0.38	0.41
0.80	0.45	0.52	0.57	0.63	0.67	0.72	0.76	0.80	0.84	0.87	0.94
1.10	0.64	0.73	0.81	0.88	0.94	1.00	1.05	1.10	1.15	1.20	1.29
1.60	0.93	1.06	1.17	1.27	1.36	1.45	1.53	1.60	1.67	1.74	1.86
2.20	1.28	1.46	1.61	1.75	1.87	1.99	2.10	2.20	2.29	2.39	2.56
2.80	1.85	2.05	2.22	2.38	2.53	2.67	2.80	2.92	3.04	3.26	

*Nominal flow rate at 1.0 bar pressure

Flow rate (l/h) vs. Pressure (bar)

0.20, 0.25 mm wall thickness dripperlines

FLOW RATE* (L/H)	PRESSURE (BAR)										
	0.3	0.4	0.5	0.6	0.7	0.8	1.0	1.1	1.3	1.5	1.7
0.35	0.20	0.22	0.25	0.27	0.29	0.31	0.35	0.37	0.40	0.42	0.45
0.72	0.40	0.46	0.52	0.56	0.61	0.65	0.72	0.75	0.82	0.87	0.93
1.05	0.61	0.70	0.77	0.84	0.90	0.95	1.05	1.10	1.18	1.26	1.33
1.60	0.93	1.06	1.17	1.27	1.36	1.45	1.60	1.67	1.80	1.92	2.03
2.20	1.28	1.46	1.61	1.75	1.87	1.99	2.20	2.29	2.47	2.64	2.79
2.80	1.85	2.05	2.22	2.38	2.53	2.67	2.80	2.92	3.15	3.36	3.55

*Nominal flow rate at 1.0 bar pressure

/ Max. Lateral length

Flow Variation (FV) expresses the flow variation between the dripper "sensing" the highest pressure and the one "sensing" the lowest pressure in an irrigation block (zone).

These drippers will not always be the first and last drippers on the dripline.

$$FV \% = (Q_{\max} - Q_{\min}) / Q_{\max} * 100$$

*International standards define 10% flow variation to be considered as uniform irrigation.

In order to calculate the maximum run lengths that can be planned for specific dripline (considering all the hydraulic factors influencing the flow within the same dripline), we use a calculation software that was developed by Netafim™ based on Darcy-Waisbach formulas + years of design experience and cooperation with academic institutes.

All the tables presented in this document are for initial reference only; the exact run length of the driplines is obtained from design software that considers various hydraulic factors in the entire system.

There might be small variance between the different software's in the market due to the calculation method and assumptions each software is using. For an initial estimate of the dripline length, the data that is presented in this document (within the tables shown) is sufficiently accurate.

Non-regulated drippers of Netafim™ will provide different flow according to the real working pressure, therefore, the influencing factors will be: the pressure that each dripper in the dripline is exposed to, and the allowed flow variation the dripline is designed to, which in most cases is defined as 10% difference in flow, according to the international standards, and / or any other limitation that the customer / planner will prefer to design while considering the crop needs and area topography.

The following tables are only displayed at one inlet pressure for each dripline, since in non-regulated drippers the flow varies according to the pressure. There might be differences in run lengths with different inlet pressures; however for an initial estimate of the dripline length, the data that is presented in this document (within the tables shown) is sufficiently accurate.

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12060 • ID 11.8 mm • Kd 0.15 • Flow rate 0.35 l/h • Inlet pressure 1.2 Bar

	SLOPE	DISTANCE BETWEEN DRIPPERS (METER)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	80	93	100	105	108	110	112
	1%	99	123	141	155	166	175	183
FLAT TERRAIN	0	122	162	197	229	259	287	313
	-1%	140	192	241	288	331	374	416
DOWNHILL	-2%	154	216	273	181	205	161	152

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12060 • ID 11.8 mm • Kd 0.15 • Flow rate 0.80 l/h • Inlet pressure 1.2 Bar

	SLOPE	DISTANCE BETWEEN DRIPPERS (METER)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	57	69	78	85	90	95	98
	1%	64	82	96	108	118	127	135
FLAT TERRAIN	0	72	96	116	136	153	169	186
	-1%	79	109	136	162	187	211	234
DOWNHILL	-2%	86	122	155	189	221	253	286

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12060 • ID 11.8 mm • Kd 0.15 • Flow rate 1.10 l/h • Inlet pressure 1.2 Bar

	SLOPE	DISTANCE BETWEEN DRIPPERS (METER)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	51	65	74	82	89	95	98
	1%	56	73	86	98	109	118	126
FLAT TERRAIN	0	61	82	100	116	131	146	158
	-1%	65	89	110	131	151	169	188
DOWNHILL	-2%	70	97	123	148	172	197	221

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12060 • ID 11.8 mm • Kd 0.15 • Flow rate 1.60 l/h • Inlet pressure 1.2 Bar

	SLOPE	DISTANCE BETWEEN DRIPPERS (METER)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	42	54	63	70	76	82	86
	1%	45	59	70	81	89	98	105
FLAT TERRAIN	0	48	65	79	92	104	116	126
	-1%	51	69	85	101	115	130	143
DOWNHILL	-2%	53	74	93	111	129	146	163

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12060 • ID 11.8 mm • Kd 0.15 • Flow rate 2.20 l/h • Inlet pressure 1.2 Bar

	SLOPE	DISTANCE BETWEEN DRIPPERS (METER)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	35	45	54	60	66	71	76
	1%	37	49	59	68	75	83	89
FLAT TERRAIN	0	40	53	64	75	85	95	103
	-1%	41	56	68	81	92	104	114
DOWNHILL	-2%	43	59	74	88	101	114	127

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12060 • ID 11.8 mm • Kd 0.15 • Flow rate 2.80 l/h • Inlet pressure 1.2 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	28	37	44	50	55	60	63
	1%	30	40	48	55	61	67	73
FLAT TERRAIN	0	31	42	52	61	68	76	83
	-1%	33	45	55	65	74	83	92
DOWNHILL	-2%	34	47	58	69	80	90	99

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12080 • ID 11.8 mm • Kd 0.15 • Flow rate 0.35 l/h • Inlet pressure 1.2 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	80	93	100	105	108	110	112
	1%	99	123	141	155	166	175	183
FLAT TERRAIN	0	122	162	197	229	259	287	313
	-1%	140	192	241	288	331	374	416
DOWNHILL	-2%	154	216	273	181	205	161	152

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12080 • ID 11.8 mm • Kd 0.15 • Flow rate 0.72 l/h • Inlet pressure 1.2 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	59	72	81	88	93	97	100
	1%	68	86	101	114	124	134	142
FLAT TERRAIN	0	77	102	125	145	164	182	198
	-1%	86	118	147	176	203	229	255
DOWNHILL	-2%	94	132	170	206	242	279	315

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12080 • ID 11.8 mm • Kd 0.15 • Flow rate 1.05 l/h • Inlet pressure 1.2 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	53	66	76	84	90	96	100
	1%	58	75	89	101	111	120	130
FLAT TERRAIN	0	63	84	103	120	136	151	165
	-1%	67	92	114	136	156	176	195
DOWNHILL	-2%	72	101	128	154	179	205	230

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12080 • ID 11.8 mm • Kd 0.15 • Flow rate 1.60 l/h • Inlet pressure 1.2 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	42	54	63	70	76	82	86
	1%	45	59	70	81	89	98	105
FLAT TERRAIN	0	48	65	79	92	104	116	126
	-1%	51	69	85	101	115	130	143
DOWNHILL	-2%	53	74	93	111	129	146	163

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12080 • ID 11.8 mm • Kd 0.15 • Flow rate 2.20 l/h • Inlet pressure 1.2 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	35	45	54	60	66	71	76
	1%	37	49	59	68	75	83	89
FLAT TERRAIN	0	40	53	64	75	85	95	103
	-1%	41	56	68	81	92	104	114
DOWNHILL	-2%	43	59	74	88	101	114	127

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 12080 • ID 11.8 mm • Kd 0.15 • Flow rate 2.80 l/h • Inlet pressure 1.2 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	28	37	44	50	55	60	63
	1%	30	40	48	55	61	67	73
FLAT TERRAIN	0	31	42	52	61	68	76	83
	-1%	33	45	55	65	74	83	92
DOWNHILL	-2%	34	47	58	69	80	90	99

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16050 • ID 16.2 mm • Kd 0.10 • Flow rate 0.35 l/h • Inlet pressure 0.9 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	82	85	87	88	88	88	89
	1%	129	146	156	162	166	168	170
FLAT TERRAIN	0	208	276	336	391	441	488	533
	-1%	269	377	476	288	235	222	216
DOWNHILL	-2%	123	106	103	102	101	101	100

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16050 • ID 16.2 mm • Kd 0.10 • Flow rate 0.80 l/h • Inlet pressure 0.9 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	65	71	74	75	76	77	78
	1%	89	107	118	127	132	137	140
FLAT TERRAIN	0	122	162	197	229	259	286	313
	-1%	153	218	281	344	407	470	231
DOWNHILL	-2%	186	103	88	84	82	81	81

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16050 • ID 16.2 mm • Kd 0.10 • Flow rate 1.10 l/h • Inlet pressure 0.9 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	65	74	79	82	84	85	86
	1%	82	101	115	125	134	140	146
FLAT TERRAIN	0	103	138	168	195	220	244	266
	-1%	121	170	218	264	309	354	399
DOWNHILL	-2%	142	208	276	98	92	90	88

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16050 • ID 16.2 mm • Kd 0.10 • Flow rate 1.60 l/h • Inlet pressure 0.9 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	57	66	72	77	80	81	83
	1%	68	86	98	109	118	125	130
FLAT TERRAIN	0	82	108	132	154	174	193	210
	-1%	92	128	162	196	228	260	291
DOWNHILL	-2%	105	151	197	244	113	99	94

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16050 • ID 16.2 mm • Kd 0.10 • Flow rate 2.20 l/h • Inlet pressure 0.9 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	50	59	66	72	74	78	79
	1%	58	73	85	95	104	111	117
FLAT TERRAIN	0	67	89	108	126	142	158	172
	-1%	74	102	128	153	177	201	225
DOWNHILL	-2%	82	116	150	184	218	252	118

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16050 • ID 16.2 mm • Kd 0.10 • Flow rate 2.80 l/h • Inlet pressure 0.9 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	44	55	62	68	73	76	80
	1%	50	64	75	85	93	101	107
FLAT TERRAIN	0	55	74	90	104	118	131	142
	-1%	60	82	102	120	137	155	171
DOWNHILL	-2%	64	88	111	133	153	173	192

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16060/16070 • ID 16.2 mm • Kd 0.10 • Flow rate 0.35 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	89	93	96	97	97	98	99
	1%	136	156	168	176	181	184	187
FLAT TERRAIN	0	209	278	338	393	444	491	536
	-1%	265	372	470	310	297	261	248
DOWNHILL	-2%	165	122	116	114	113	112	112

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16060/16070 • ID 16.2 mm • Kd 0.10 • Flow rate 0.80 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	65	71	74	75	76	77	78
	1%	89	107	118	127	132	137	140
FLAT TERRAIN	0	122	162	197	229	259	286	313
	-1%	153	218	281	344	407	470	231
DOWNHILL	-2%	186	103	88	84	82	81	81

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16060/16070 • ID 16.2 mm • Kd 0.10 • Flow rate 1.10 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	65	74	79	82	84	85	86
	1%	82	101	115	125	134	140	146
FLAT TERRAIN	0	103	138	168	195	220	244	266
	-1%	121	170	218	264	309	354	399
DOWNHILL	-2%	142	208	276	98	92	90	88

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16060/16070 • ID 16.2 mm • Kd 0.10 • Flow rate 1.60 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	57	66	72	77	80	81	83
	1%	68	86	98	109	118	125	130
FLAT TERRAIN	0	82	108	132	154	174	193	210
	-1%	92	128	162	196	228	260	291
DOWNHILL	-2%	105	151	197	244	113	99	94

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16060/16070 • ID 16.2 mm • Kd 0.10 • Flow rate 2.20 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	50	59	66	72	74	78	79
	1%	58	73	85	95	104	111	117
FLAT TERRAIN	0	67	89	108	126	142	158	172
	-1%	74	102	128	153	177	201	225
DOWNHILL	-2%	82	116	150	184	218	252	118

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16060/16070 • ID 16.2 mm • Kd 0.10 • Flow rate 2.80 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	44	55	62	68	73	76	80
	1%	50	64	75	85	93	101	107
FLAT TERRAIN	0	55	74	90	104	118	131	142
	-1%	60	82	102	120	137	155	171
DOWNHILL	-2%	64	88	111	133	153	173	192

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16080/16100 • ID 16.2 mm • Kd 0.10 • Flow rate 0.35 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	89	93	96	97	97	98	99
	1%	136	156	168	176	181	184	187
FLAT TERRAIN	0	209	278	338	393	444	491	536
	-1%	265	372	470	310	297	261	248
DOWNHILL	-2%	165	122	116	114	113	112	112

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16080/16100 • ID 16.2 mm • Kd 0.10 • Flow rate 0.72 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	76	85	89	92	94	95	95
	1%	101	122	137	148	157	163	168
FLAT TERRAIN	0	132	176	214	248	280	311	339
	-1%	162	228	292	356	418	481	544
DOWNHILL	-2%	192	284	120	110	106	104	102

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16080/16100 • ID 16.2 mm • Kd 0.10 • Flow rate 1.05 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	73	85	93	98	101	104	105
	1%	90	112	128	142	152	161	168
FLAT TERRAIN	0	108	144	176	205	231	256	279
	-1%	124	173	219	264	308	351	394
DOWNHILL	-2%	142	205	268	333	128	119	114

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16080/16100 • ID 16.2 mm • Kd 0.10 • Flow rate 1.60 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	62	74	82	89	93	97	98
	1%	72	91	106	119	129	138	146
FLAT TERRAIN	0	83	110	134	156	176	195	214
	-1%	91	126	159	190	220	250	279
DOWNHILL	-2%	102	145	187	229	271	313	150

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16080/16100 • ID 16.2 mm • Kd 0.10 • Flow rate 2.20 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	53	65	74	81	85	90	93
	1%	60	77	90	102	112	120	128
FLAT TERRAIN	0	68	90	110	128	144	160	174
	-1%	73	101	126	150	173	195	218
DOWNHILL	-2%	80	113	144	175	205	236	266

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 16080/16100 • ID 16.2 mm • Kd 0.10 • Flow rate 2.80 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	44	55	62	68	73	76	80
	1%	50	64	75	85	93	101	107
FLAT TERRAIN	0	55	74	90	104	118	131	142
	-1%	60	82	102	120	137	155	171
DOWNHILL	-2%	64	88	111	133	153	173	192

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22050/22060/22070 • ID 22.2 mm • Kd 0.01 • Flow rate 0.35 l/h • Inlet pressure 0.8 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	78	78	79	79	79	79	80
	1%	146	151	154	155	156	157	157
FLAT TERRAIN	0	379	492	593	684	769	849	925
	-1%	215	189	183	181	180	179	179
DOWNHILL	-2%	89	89	88	89	88	88	89

Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22050/22060/22070 • ID 22.2 mm • Kd 0.01 • Flow rate 0.80 l/h • Inlet pressure 0.8 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	75	77	78	78	78	78	78
	1%	125	137	144	148	150	151	153
FLAT TERRAIN	0	224	291	350	405	455	502	546
	-1%	334	482	189	175	169	165	163
DOWNHILL	-2%	85	81	80	80	79	79	79

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22050/22060/22070 • ID 22.2 mm • Kd 0.01 • Flow rate 1.10 l/h • Inlet pressure 0.8 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	81	85	87	88	89	89	90
	1%	123	141	151	158	163	167	169
FLAT TERRAIN	0	190	247	298	344	387	427	465
	-1%	256	363	469	235	197	187	182
DOWNHILL	-2%	100	89	86	86	85	84	84

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22050/22060/22070 • ID 22.2 mm • Kd 0.01 • Flow rate 1.60 l/h • Inlet pressure 0.8 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	76	82	84	87	87	88	89
	1%	107	125	138	146	152	157	161
FLAT TERRAIN	0	150	195	235	272	305	337	367
	-1%	190	266	339	412	486	561	207
DOWNHILL	-2%	237	98	90	88	86	85	85

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22050/22060/22070 • ID 22.2 mm • Kd 0.01 • Flow rate 2.20 l/h • Inlet pressure 0.8 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	70	77	82	84	85	86	87
	1%	93	111	124	134	142	147	152
FLAT TERRAIN	0	123	160	192	222	250	275	301
	-1%	149	206	260	314	367	420	474
DOWNHILL	-2%	179	259	99	92	89	88	86

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22050/22060/22070 • ID 22.2 mm • Kd 0.01 • Flow rate 2.80 l/h • Inlet pressure 0.8 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	60	67	70	73	74	76	77
	1%	77	93	105	114	121	126	130
FLAT TERRAIN	0	99	130	157	181	204	225	246
	-1%	117	159	198	234	269	304	337
DOWNHILL	-2%	130	180	124	116	103	99	96

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22080/22100 • ID 22.2 mm • Kd 0.01 • Flow rate 0.35 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	96	97.8	98	99	99	99	99
	1%	174	184	189	192	193	194	195
FLAT TERRAIN	0	383	498	600	693	779	860	937
	-1%	303	258	238	231	228	226	225
DOWNHILL	-2%	114	112	111	111	111	111	111

Due to lateral filling time and flushing effectiveness it is not recommended to exceed 800 meters lateral length

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22080/22100 • ID 22.2 mm • Kd 0.01 • Flow rate 0.72 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	75	77	78	78	79	78	78
	1%	128	140	145	149	151	153	154
FLAT TERRAIN	0	239	311	375	433	487	538	586
	-1%	367	243	180	171	166	164	162
DOWNHILL	-2%	83	81	80	80	79	79	78

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22080/22100 • ID 22.2 mm • Kd 0.01 • Flow rate 1.05 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	82	86	87	88	89	90	90
	1%	126	142	152	160	164	167	170
FLAT TERRAIN	0	196	255	308	355	399	440	481
	-1%	267	379	491	218	193	185	180
DOWNHILL	-2%	98	89	86	85	85	84	84

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22080/22100 • ID 22.2 mm • Kd 0.01 • Flow rate 1.60 l/h • Inlet pressure 1.0 Bar

	DISTANCE BETWEEN DRIPPERS (METER)							
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	76	82	84	87	87	88	89
	1%	107	125	138	146	152	157	161
FLAT TERRAIN	0	150	195	235	272	305	337	367
	-1%	190	266	339	412	486	561	207
DOWNHILL	-2%	237	98	90	88	86	85	85

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22080/22100 • ID 22.2 mm • Kd 0.01 • Flow rate 2.10 l/h • Inlet pressure 1.0 Bar

		DISTANCE BETWEEN DRIPPERS (METER)						
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	70	77	82	84	85	86	87
	1%	93	111	124	134	142	147	152
FLAT TERRAIN	0	123	160	192	222	250	275	301
	-1%	149	206	260	314	367	420	474
DOWNHILL	-2%	179	259	99	92	89	88	86

Max. lateral length (meters) at different slopes - 10% flow variation

Streamline™ X • 22080/22100 • ID 22.2 mm • Kd 0.01 • Flow rate 2.80 l/h • Inlet pressure 1.0 Bar

		DISTANCE BETWEEN DRIPPERS (METER)						
	SLOPE	0.20	0.30	0.40	0.50	0.60	0.70	0.80
UPHILL	2%	60	67	70	73	74	76	77
	1%	77	93	105	114	121	126	130
FLAT TERRAIN	0	99	130	157	181	204	225	246
	-1%	117	159	198	234	269	304	337
DOWNHILL	-2%	130	180	124	116	103	99	96